

IN THE CLAIMS

1. (Currently Amended) A method of providing access to a bus, comprising:

~~receiving a request for device access to the bus;~~
~~selecting the request according to a priority associated with the request;~~

~~generating a control signal in response to selection of the request;~~

~~enabling a switch associated with the request to couple a device associated with the request to the bus in response to the control signal, wherein the device did not provide a load on the bus prior to the switch coupling the device to the bus.~~

receiving a plurality of device access requests for the bus, each of the plurality of device access requests being received from one of a plurality of devices not coupled to the bus, each of the plurality of devices having a switch associated therewith;

selecting a particular one of the plurality of device access requests according to a predetermined priority protocol;

generating a control signal corresponding to the selected particular one of the plurality of device access requests;

providing the control signal to a particular one of the plurality of devices that sent the selected particular one of the plurality of device access requests, the control signal enabling the switch associated with the particular one of the plurality of devices to couple the particular one of the plurality of devices to the bus;

selecting a next one of the plurality of device access requests according to the predetermined priority protocol;

generating a control signal corresponding to the selected next one of the plurality of device access requests;

providing the control signal to a next one of the plurality of devices that sent the selected next one of the plurality of device access requests, the control signal enabling the switch associated with the next one of the plurality of devices to couple the next one of the plurality of devices to the bus prior to an end of the particular one of the plurality of devices being coupled to the bus.

2. (Original) The method of Claim 1, wherein the bus is a PCI bus.

3. (Original) The method of Claim 2, wherein the PCI bus operates at a frequency of at least 66 MHz.

4. (Currently Amended) The method of Claim 1, wherein the ~~request is~~ plurality of device access requests are received from ~~a device~~ devices desiring to communicate over the bus.

5. (Canceled).

6. (Canceled).

7. (Currently Amended) The method of ~~Claim 6~~ Claim 1, further comprising:

determining an end for the particular one of the plurality of devices to be coupled to the bus;

initiating ~~coupling~~ access of the next one of the plurality of devices to the bus in response to the end for the particular one of the plurality of devices to be coupled to the bus.

8. (Previously Presented) The method of Claim 7, further comprising:

generating a disabling control signal in response to the end for the particular one of the plurality of devices to be coupled to the bus;

decoupling the particular one of the plurality of devices from the bus in response to the disabling control signal.

9. (Original) The method of Claim 1, further comprising:
limiting a number of generated control signals in order to control a load on the bus.

10. (Previously Presented) The method of Claim 1, further comprising:

generating a disable control signal for a request not selected in order to prevent coupling of an associated device to the bus.

11. (Previously Presented) A system for providing access to a bus, comprising:

a bus controller;

a plurality of processing devices capable of being coupled to the bus controller by a bus;

a plurality of enabling switches on the bus, each enabling switch coupled to a corresponding processing device, each enabling switch determining whether the corresponding processing device is coupled to the bus in response to a control signal from the bus controller; ~~wherein processing devices not coupled to the bus by their respective enabling switches do not provide a load on the bus~~

wherein the bus control receives a plurality of requests from the plurality of processing devices, the bus controller operable to select a highest priority request, the bus controller operable to generate a first control signal for a first enabling switch associated with a first processing device having the highest priority request, the first enabling switch coupling the first processing device to the bus for access thereto;

wherein the bus controller is operable to select a next highest priority request, the bus controller operable to generate a second control signal for a second enabling switch associated with a second processing device having the next highest priority request, the second enabling switch coupling the second processing device to the bus, the bus controller allowing the second processing device to be coupled to the bus prior to decoupling the first processing device from the bus.

12. (Previously Presented) The system of Claim 11, wherein the bus controller allows simultaneous coupling to the bus by a predetermined number of the plurality of processing devices in order to limit a load on the bus.

13. (Previously Presented) The system of Claim 11, wherein the bus controller receives a plurality of device access requests from the plurality of processing devices for coupling to the bus.

14. (Previously Presented) The system of Claim 13, wherein the bus controller arbitrates the plurality of device access requests from the plurality of processing devices according to a predetermined protocol.

15. (Original) The system of Claim 11, wherein the bus is a PCI bus.

16. (Original) The system of Claim 15, wherein the PCI bus operates at a frequency of approximately 66 MHz.

17. (Currently Amended) A PCI bus, comprising:

a plurality of pass transistors, each pass transistor operable to provide coupling of an associated processing device to the bus, each pass transistor operable to receive a control signal to couple and decouple its associated processing device to and from the bus, ~~wherein processing devices not coupled to the bus by their associated pass transistor do not provide a load on the bus~~ wherein a first pass transistor couples a first processing device to the bus for access thereto in response to a first control signal, a second pass transistor couples a second processing device to the bus in response to a second control signal prior to decoupling of the first processing device from the bus upon an end of access thereto.

18. (Original) The PCI bus of Claim 17, wherein a particular pass transistor receives an enable control signal in response to an access request sent by its associated processing device.

19. (Previously Presented) The PCI bus of Claim 17, wherein a particular pass transistor is operable to decouple its associated processing device from the bus such that the particular processing device does not appear to be coupled to the PCI bus in order to reduce a load on the bus.

20. (Original) The PCI bus of Claim 17, wherein each of the processing devices is operable to communicate at a 66 MHz rate.